MAX-LED KARTA PRODUKTOWA

AR111
14W SMD



A+

www.max-led.pl

MAX-LED WARRANTY 3 years EXCLUSIVE

ZASTOSOWANIE

- Oświetlenie wnętrz sklepów
- Oświetlenie architektoniczne
- Oświetlenie nastrojowe pomieszczeń

Dane techniczne podstawowe


Temperatura barwowa	EAN	Strumień świetlny
4500K biała neutralna	5901812464972	1000 lm *

Dane techniczne wspólne

Trzonek	G53
Moc znamionowa	14 W
Moc odpowiednika	75 W
Napięcie	12V AC/DC
Kąt świecenia	25º
Klasa szczelności obudowy	-
Współczynnik oddawania barw	Ra ≥ 80
Współczynnik mocy	PF 0,7
Sposób montażu	-
Możliwość ściemniania	NIE
Trwałość	50 000 h
Liczba cykli włączeniowych	20 000
Typ diod LED	SMD
Materiał	metal
Kolor obudowy	biały
Czas rozruchu	<0,2s
Czas rozgrzewania do (60%), do (95%)	<2s

* Całkowity strumień świetlny źródła światła za kloszem przy temp. otoczenia 25°C. Tolerancja strumienia świetlnego +/- 10%.


Rysunek techniczny




Wymiary produktu

Ø - wymiar	111 [mm]
L - wymiar	58 [mm]

Diagram rozkładu natężenia światła



Rysunek poglądowy sposób pakowania



Opakowanie jednostkowe produktu

ox - wymiar	111 [mm]
oy - wymiar	111 [mm]
oz - wymiar	111 [mm]
Waga	315 [gr]

Opakowanie zbiorcze produktów

Typ pakowania O(XYZ)	5x2x2
Ilość sztuk	20
OX - wymiar	590 [mm]
OY - wymiar	243 [mm]
OZ - wymiar	220 [mm]
Waga	6,7 [kg]

WSZELKIE PRAWA ZASTRZEŻONE 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

Zdjęcia produktów i niektóre parametry techniczne umieszczone w karcie produktu mogą nieznacznie odbiegać od produktów znajdujących się w sprzedaży. Zastrzegamy sobie prawo do błędów w druku.

MAX-LED PRODUCT CARD

AR111
14W SMD



A+

www.max-led.pl

MAX-LED WARRANTY 3 years EXCLUSIVE

APPLICATION

- in-store lighting
- architectural lighting
- mood lighting of premisesg

Basic technical data


Color temperature	EAN	Luminous flux
4500K neutral white	5901812464972	1000 lm *

Common technical data


Base	G53
Wattage	14 W
Equivalent	75 W
Voltage	12V AC/DC
Beam angle	25º
IP protocol	-
Color Rendering Index	Ra ≥ 80
Power factor	PF 0.7
Mounting	-
Dimming	No
Lifespan	50 000 h
Number of switching cycles	20 000
LED type	SMD
Material	plastic
Housing color	white
Starting time	<0,2s
Warm-up time (60%), do (95%)	<2s

* The total luminous flux of the light source behind the shade at ambient temp. 25 ° C. Tolerance flux +/- 10%.

Technical drawing




Illustrative method of packaging



Product dimensions

Ø - dimension	111 [mm]
L - dimension	58 [mm]

Diagram of light intensity distribution



The unit package of the product

ox - dimension	111 [mm]
oy - dimension	111 [mm]
oz - dimension	111 [mm]
Weight	315 [gr]

Opakowanie zbiorcze produktów

Packaging type O(XYZ)	5x2x2
Quantity	20
OX - dimension	590 [mm]
OY - dimension	243 [mm]
OZ - dimension	220 [mm]
Weight	6.7 [kg]

RoHS Compliance

ALL RIGHTS RESERVED 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

THE PICTURES OF PRODUCTS IN THE PRODUCT CARD MAY DIFFER FROM THE ACTUAL PRODUCTS. WE RESERVE THE RIGHT TO PRINTING MISTAKES AND ERRORS. THE SHAPE AND TECHNICAL DATE OF ALL PRODUCTS FROM THIS PRODUCT CARD ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.